




Are you looking for a fast and efficient way to seed or overseed your golf course or sports pitch? With the Combiseeder we offer you both solutions, as well as the facility to seed multiple types of grass. The Combiseeder has two spiked rollers that open up the soil and seed is then spread accurately across the full width, in and around the holes. Two drag brushes incorporate the seed into the holes and this method results in minimal surface disruption. The Combiseeder is also uniquely equipped with two water tanks that allow you to ballast the machine, to aid spike penetration on harder ground.



The seed dosing system gives you the opportunity to divide the amount of seed accurately on the soil. It is possible to seed from 3 up to 50 grams per square meter. Using the lever behind the seed hopper you can adjust the opening for the seed dosing.



The conical spike rollers produce 1500 holes per square meter, opening up the soil and the seed falls behind the first roller. The spike rings are loosely mounted on a rotor tube so they can move separately, enabling you to make turns without damaging the grass. Behind the rollers, the two brushes sweep seed and topdressing, with the first brush being adjustable for pressure and the second following the contours.

THE WORKER IS KING



Туре	CS120	CS160	CS200	CS240
Working width	120 cm / 47"	160 cm / 63"	200 cm / 79"	240 cm / 95"
Working depth	3-50gms / m2	3-50gms / m2	3-50gms / m2	3-50gms / m2
Capacity seed hopper	150 l	200 I	250 l	300 l
Dimensions (I x w x h)	140 x 130 x 100 cm / 56 x 52 x 40"	140 x 170 x 100 cm/ 56 x 67 x 40"	140 x 210 x 100 cm / 56 x 83 x 40"	140 x 250 x 100 cm / 56 x 99 x 40"
Weight	500 kg / 1023 lbs	660 kg / 1455 lbs	830 kg / 1850 lbs	990 kg / 2183 lbs
Power requirement	> 35 hp	> 45 hp	> 55 hp	> 65
Linkage	Standard three-point hitch cat I	Standard three-point hitch cat II	Standard three-point hitch cat II	Standard three-point hitch cat II

THE WORKER IS KING

GKB Machines bv Augustapolder 13 2992 SR Barendrecht, the Netherlands t +31 (0)180 64 29 22 e info@gkbmachines.com i www.gkbmachines.com