

Mete-R-Matic® XL

Tow-Type Topdresser



Ground-drive system means no tow vehicle calibration required; just hook up and go.



Easy on/off switch.



Patented continuous Chevron belt ensures uniform application.

The Ultimate in Topdressing Productivity

At 60.75 cubic feet, the hopper capacity of the Mete-R-Matic® XL is three times the size of the Mete-R-Matic III, for less reloading and increased efficiency on large turf areas.

- Patented ground-drive and Chevron® belt combines for the most consistent and uniform application in the industry.
- Patented Chevron belt can consistently handle all types of material such as compost, sand, peat, crumb rubber and calcine clays.
- Larger capacity hopper, that can easily be filled with a front-end loader, requires fewer trips to refill.



Wide hopper capacity means less time reloading.

Specifications

Model	Mete-R-Matic XL (#85460)
Drive	Wheels are driven by the ground; all six tires mechanically drive the conveyor and brush; no engine; no hydraulic system
Hopper Capacity	60.75 ft ³ (1.72 m ³ ; 2.25 yd ³), galvanized panels
Hopper Size	Top: 80" x 65.5" (2.03 m x 1.66 m) Bottom: 60" x 46" (1.5 m x 1.17 m) Depth: 18 1/2" (0.47 m)
Payload	6,000 lb (2,721 kg)
Spreading Width	60" (1.5 m)
Topdressing Speed	Up to 8 MPH (12.8 km/h) loaded
Conveyor Belt	Wide rubber composition with patented Chevron belt 60" (1.5 m)
Metering Gate	Taintor gate design is easily adjusted and provides a uniform opening up to 2 1/4" (57 mm)
Brush	9" (228 mm) diameter, polypropylene bristle
Controls	Electrically operated clutch for conveyor and brush drive. Metering gate adjusted by hand.
Clutch	The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle
Wheels & Tires	Two, 33" x 15.50" – 16.5" flotation tires
Hitch	Adjustable height clevis 1" pin hitch
Empty Weight	2,110 lb (957 kg) tow vehicle minimum 30 HP tractor (refer to Operator's Manual for additional requirements)
Electrical Requirements	12 volt DC, negative ground (<i>electrical power provided by tow vehicle</i>)

METE-R-MATIC is a registered trademark of Turfco Manufacturing, Inc.