

TORO

MH-400

The MH-400 handles everything: Topdressing, Cross-Conveyor, Material Delivery & Hauling/Transport. Designed to perform everyday as part of your maintenance program. By being an integral component to daily tasks the MH-400 reduces labor, saves time and cuts operating costs. Optional wireless remote control available.



MH-400, MODELS 44930 & 44931 / MH-400 WIRELESS, MODELS 44933 & 44934*	
GENERAL	Hopper Capacity: 4 yd ³ (3.06 m ³) Main Conveyor Belt: One Piece Vulcanized, Self Tracking, 30" wide Controls: Standard Hydraulic (SH) or Electronic Hydraulic (EH)
WEIGHT	Base Model: 3,000 lbs (1,360 kg) - empty with no options installed
CHASSIS	Payload (tare): 11,800 lbs (5,353 kg) GVWR: 14,800 lbs (6,713 kg) Suspension: 4 Wheel Walking Beam with 10 ply turf tires Tire Size: 33 x 16 x 16.1 in (82.5 x 40 x 40.25 cm) 10 ply Brakes (electric) - Optional 2 or 4 wheel
DIMENSIONS	Length 190 in (4.8 m) Height 86 in (2.2 m) Width 78 in (1.98 m)
TOW VEHICLE REQUIREMENTS	Towing Capacity: 15,850 lbs (7,175 kg) - maximum payload Minimum Power: 45 Hp (34 Kw)
HYDRAULICS	Recommended Flow (min no options installed): 6 US gal/min (23 L/min) Recommended Flow (min options installed): 10 US gal/min (38 L/min) Recommended Input Pressure (min): 2,000 psi (138 bar)
WARRANTY	Two-year limited warranty. Refer to operators manual for further details.
CE REQUIREMENTS	Meets the CE requirements for the EU

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

