OXYMAX® Directional Flow Aeration System

Give the aquatic manager a solution to water quality problems when no fountain spray pattern is desired. These silent, vertical mixers are environmentally friendly and will not disturb your aquatic landscape.

Oxymax® Aeration Systems work from the bottom of the pond, completely submerged, out of sight and silent. It couples an electric motor to a propeller water transport system. The oxygen-depleted water is moved rapidly from the bottom of the pond directly and efficiently to the surface. The cooler, denser water absorbs oxygen as it quickly spreads across the pond. It returns down through the de-stratified layers, providing equal distribution of oxygenated water.

System Features

• Totally out of sight and silent, submerged to bottom

 Lightweight, small size makes it highly mobile and easily relocated for spot problems (1/2 HP)


 Ideal for fish impoundments, keeps ponds open year round (where applicable) eliminating winter kill

No possible freeze damage - aerator is totally submerged

 Submerged motor and seals lubricated by non-toxic food grade oil for longer life

• 1/2 to 5 HP, 1 and 3 phase motors

- 3 year warranty, 1 HP and larger
- 2 year warranty, 1/2 HP
- Easily adapts to any pond 2.5' to 20' deep
- Low-profile float mounted below waterline
- Quality stainless steel components



Oxymax® Sizing

General Rule of Thumb: 1 HP per surface acre. Increase number of units for ponds with restricted circulation and/or severe nutrient load conditions.



