



Topdresser 2500

This 25 cu. ft. Topdresser gives you precise control and consistently delivers an even application—whether light or heavy topdressing is desired.



TOPDRESSER 2500, MODEL 44507*					
HOPPER CAPACITY	25 cu. ft. (698 liter) or up to 2,050 lbs. (930 kg).				
SPREADING WIDTH	60" (152 cm)				
TOP DRESSING SPEED	Variable to desired application rate. 2-8 mph (3-13 km/h).				
TRANSPORT SPEED	Up to 12 mph (19 km/h). Optional brake kit available.				
CONVEYOR BELT	Seamless 60" (152 cm) wide belt, polyester mono-filament interwoven material w/gray PVC "v-pattern" traction surface.				
METERING GATE	Infinitely variable from closed to 3.5" (9 cm) opening for light to heavy applications. Flexible edge and spring release.				
CONTROLS	12-volt on/off switch at operator's position to engage conveyor and brush. Metering gate runs full width in front of brush.				
DRIVE	Hydraulic with chain driven pumps. Belt motor with chain reduction. Brush motor direct drive. Electric hydraulic solenoid control to activate topdress motors. Closed loop hydraulic system with charge pump and 25 micron filtration.				
TIRES	(4) 18 x 10.5-8, 4-ply ribbed, high floatation turf tires on oscillating axle sets.				
DIMENSIONS /WEIGHT	Height 43" (109 cm)	Width 72.5" (184 cm)	Overall Length 97.5" (248 cm)	Shipping Weight 1,454 lbs. (659 kg)	Maximum Weight 3,500 lbs. (1,589 kg)
WARRANTY	Two-year limited warranty. refer to Operator's Manual for further details.				

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

