

**TORO**

**Count on it.**

# REELMASTER® 5010 SERIES COMPETITIVE COMPARISON



PRODUCT COMPARISON	Toro RM5210	Toro RM5410	Toro RM5510	Toro RM5610	John Deere 3225C*	John Deere 3235C*	Jacobsen 5LF-1880*	Jacobsen LF-3400/3407*	Jacobsen LF-3800*
Engine Performance									
Manufacturer	Kubota	Kubota	Kubota	Kubota	John Deere	John Deere	Kubota	Kubota	Kubota
Rated Output	28 hp	35.5 hp	35.5 hp	44.2 hp (Turbo)	32 hp	41 hp	26 hp 33 hp (Turbo)	33.5 hp 44.2 hp (Turbo)	35.5 hp 44.2 hp (Turbo)
Fuel Tank Capacity	13.5 gal.	13.5 gal.	13.5 gal.	13.5 gal.	18 gal.	18 gal.	12 gal.	17 gal.	17 gal.
Traction Unit Specifications									
Drive System	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors	Hydro w/ Wheel Motors
Traction Drive	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.	2WD Std. 4WD Opt.
Transport Speed	0-10 mph	0-10 mph	0-10 mph	0-10 mph	0-11 mph	0-11 mph	0-10.5 mph (2WD) 0-6 mph (4WD)	0-12 mph (2WD) 0-7.5 mph (4WD)	0-12 mph (2WD) 0-7.5 mph (4WD)
Mowing Speed	0-8 mph	0-8 mph	0-8 mph	0-8 mph	0-7 mph (2WD) 0-6.5 mph (4WD)	0-7 mph	0-6 mph (4WD)	Not Published	Not Published
Steering Type	Power	Power	Power	Power	Power	Power	Power	Power	Power
Control Placement	Control Arm	Control Arm	Control Arm	Control Arm	Control Arm	Control Arm	Over the Side	Over the Side	Over the Side
Service/Parking Brake	Pedal w/ Lock Drum Brakes	Pedal w/ Lock Drum Brakes	Pedal w/ Lock Drum Brakes	Pedal w/ Lock Drum Brakes	Pedal w/ Lock Disk Brakes	Pedal w/ Lock Disk Brakes	Pedal w/ Lock Disk Brakes	Pedal w/ Lock Disk Brakes	Pedal w/ Lock Disk Brakes
Front Tires	F - 24 x 13-12 R - 20 x 10-10	F - 26.5 x 14-12 R - 20 x 12-10	F - 26.5 x 14-12 R - 20 x 12-10	F - 26.5 x 14-12 R - 20 x 12-10	F - 26 x 14-12 R - 20 x 10-8	F - 26 x 14-12 R - 20 x 10-8	F - 24 x 13-12 R - 18 x 9.5-8	F - 26.5 x 14-12 R - 20 x 10-8	F - 26.5 x 14-12 R - 20 x 10-8
ROPS (2 Post)	Opt. (2WD) Std. (4WD)	Opt. (2WD) Std. (4WD)	Opt. (2WD) Std. (4WD)	Opt. (2WD) Std. (4WD)	Standard	Standard	Optional	Optional	Optional
Dimensions									
Height	62 in.	63 in.	63 in.	63 in.	57 in.	57 in.	56 in.	58.75 in.	58.75 in.
Length	111 in.	111 in.	111 in.	111 in.	110 in.	110 in.	100 in.	108 in.	108 in.
Transport Width	90 in.	90 in.	92 in.	92 in.	86.5 in.	86.5 in.	88 in.	87 in.	87 in.
Operational Width	113.5 in.	113.5 in.	116 in.	116 in.	110 in.	110 in.	88 in.	115 in.	115 in.
Weight	2,396 lbs. (2WD) 2,506 lbs. (4WD)	2,505 lbs. (2WD) 2,615 lbs. (4WD)	2,693 lbs. (2WD) 2,803 lbs. (4WD)	2,813 lbs. (2WD) 2,923 lbs. (4WD)	3260 lbs.	3324 lbs.	2,115 lbs. (2WD) 2,200 lbs. (4WD)	2,580 lbs. (2WD) 2,705 lbs. (4WD)	2,790 lbs. (2WD) 2,915 lbs. (4WD)
Cutting Units									
Individual Width	22 in.	22 in.	22 in.	22 in.	22 in.	22 in.	18 in.	22 in.	22 in.
Total Width of Cut	100 in.	100 in.	100 in.	100 in.	100 in.	100 in.	80 in.	100 in.	100 in.
Reel Diameter	5 in.	5 in.	7 in.	7 in.	5 or 7 in.	5 or 7 in.	5 in.	5 or 7 in.	7 in.
Number of Blades	8	8	8 or 11	8 or 11	7 (5 in.) 5, 8, 10 (7 in.)	7 (5 in.) 5, 8, 10 (7 in.)	8 or 11	7, 9 or 11	9 or 11
Height of Cut Range	0.25-1.0 in.	0.25-1.0 in.	0.25-1.0 in.	0.25-1.0 in.	0.25-1.125" (5") 0.25-3" (7")	0.25-1.125" (5") 0.25-3" (7")	0.3-0.7 in.	0.375-0.75 in.	0.375-1.125 in.
High Height of Cut Limit	1.5 in.	1.5 in.	2 in.	2 in.	1.125 in. (5 in.) 3 in. (7 in.)	1.125 in. (5 in.) 3 in. (7 in.)	0.937 in.	1.187 in.	1.562 in.
Bedknife/Reel Adjustment	Bedknife to reel	Bedknife to reel	Bedknife to reel	Bedknife to reel	B-to-R (5 in.) R-to-B (7 in.)	B-to-R (5 in.) R-to-B (7 in.)	Bedknife to reel	Bedknife to reel	Bedknife to reel
Accessories									
Groomer	■	■	■	■	■	■	■	■	■
Rear Roller Brush	■	■	■	■	■	■	■	■	■
Baskets	■	■	■	■	■	■	■	■	■
5" Verticutter	■	■	■	■	■	■	■	■	■
7" Verticutter	■	■	■	■	■	■	■	■	■
Hydraulic Oil Monitor	■	■	■	■	■	■	■	■	■

\*Sources: John Deere web site, Jacobsen web site and printed materials. Data not independently verified by The Toro Company.