

Product data sheet

Greens TERRA SPIKE®



Deep aeration and removal of compaction to a depth of 12".

The Greens TERRA SPIKE® is dedicated to Golf Greens but also other fine turfs. High performance and excellent working quality, a very user friendly setup, technical reliability and high durability were the main tasks in development and were successfully realised.

The SYSTEM TERRA SPIKE® offers a wide range of tools and attachments also for the Greens TERRA SPIKE®. The Greens TERRA SPIKE® can be extended to a multifunctional machine which can be used throughout the whole year.

TECHNICAL DATA

Greens TERRA SPIKE®

Model:	G 6/135	G 6/160	
Working width in inches:	53"	63"	
Weight in lbs. (approx.):	1289	1488	
Working depth in inches with solid tines/hollow tines up to:	12" / 7 ½"	12" / 7 ½"	
Dimensions L / W / H in inches (approx.):	42" / 72" / 53"	42" / 81" / 53"	
Mounting:	rear three point cat. I		
QuickSet / QuickFit / PowerPack / VibraStop:	standard		
Minimum required tractor power (recommended):	20 HP	20 HP	
Crankshaft speed:	175 RPM	232 RPM	290 RPM
Maximum admissible tractor power:	40 HP	40 HP	40 HP
Minimum tractor lifting capacity with standard attachment in lbs.:	2050	2205	
Tractor PTO speed:	540 RPM		
Solid tines Ø in inches:	3/16", 5/16", 1/2", 3/4"		
Hollow tines Ø in inches:	1/2", 5/8", 3/4", 1"		
Rear roller:	standard		
Turf retainer:	optional		
Swath board:	optional		
Hydraulic rotary brush:	optional		
Additional weights:	optional		
Multi-tine holders for solid tines 3/16", 5/16" and 1/2":	optional		
Multi-tine holders for hollow tines of 1/2", 5/8" and 3/4":	optional		

Area coverage in continuous operation in square feet per hour at a crankshaft speed of:

290 RPM; at 0.6 mph; square hole spacing 2" (approx.):	14531 sq.ft./hr	-
290 RPM; at 1.25 mph; square hole spacing 4" (approx.):	29062 sq.ft./hr	-
290 RPM; at 0.7 mph; square hole spacing 2 ½" (approx.):	-	20667 sq.ft./hr
290 RPM; at 1.50 mph; square hole spacing 5" (approx.):	-	30569 sq.ft./hr

Descriptions and illustrations are non-binding. We reserve the right to modify the construction and design.

